proportions, ASTM D6866–08 (incorporated by reference, see §98.7) and ASTM D7459–08 (incorporated by reference, see §98.7) may be used to determine the biogenic portion of the CO₂ emissions in every calendar quarter in which biomass and non-biogenic fuels are co-fired in the unit. Follow the procedures in paragraph (d) of this section. If the primary fuel for multiple units at the facility consists of tires, and the units are fed from a common fuel source, testing at only one of the units is sufficient.

- (f) The records required under \$98.3(g)(2)(i) shall include an explanation of how the following parameters are determined from company records (or, if applicable, from the best available information):
- (1) Fuel consumption, when the Tier 1 and Tier 2 Calculation Methodologies are used, including cases where \$98.36(c)(4) applies.
- (2) Fuel consumption, when solid fuel is combusted and the Tier 3 Calculation Methodology is used.
- (3) Fossil fuel consumption when $\S98.33(e)(2)$ applies to a unit that uses CEMS to quantify CO_2 emissions and that combusts both fossil and biomass fuels.
- (4) Sorbent usage, when §98.33(d) applies.
- (5) Quantity of steam generated by a unit when §98.33(a)(2)(iii) applies.
- (6) Biogenic fuel consumption and high heating value, as applicable, under §§ 98.33(e)(5) and (e)(6).
- (7) Fuel usage for CH₄ and N₂O emissions calculations under §98.33(c)(4)(ii).
- (8) Mass of biomass combusted, for premixed fuels that contain biomass and fossil fuels under §98.33(e)(1)(iii).

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79146, Dec. 17, 2010]

§ 98.35 Procedures for estimating missing data.

Whenever a quality-assured value of a required parameter is unavailable (e.g., if a CEMS malfunctions during unit operation or if a required fuel sample is not taken), a substitute data value for the missing parameter shall be used in the calculations.

(a) For all units subject to the requirements of the Acid Rain Program, and all other stationary combustion

units subject to the requirements of this part that monitor and report emissions and heat input data year-round in accordance with part 75 of this chapter, the missing data substitution procedures in part 75 of this chapter shall be followed for CO₂ concentration, stack gas flow rate, fuel flow rate, high heating value, and fuel carbon content.

- (b) For units that use the Tier 1, Tier 2, Tier 3, and Tier 4 Calculation Methodologies, perform missing data substitution as follows for each parameter:
- (1) For each missing value of the high heating value, carbon content, or molecular weight of the fuel, substitute the arithmetic average of the qualityassured values of that parameter immediately preceding and immediately following the missing data incident. If the "after" value has not been obtained by the time that the GHG emissions report is due, you may use the "before" value for missing data substitution or the best available estimate of the parameter, based on all available process data (e.g., electrical load, steam production, operating hours). If, for a particular parameter, no qualityassured data are available prior to the missing data incident, the substitute data value shall be the first quality-assured value obtained after the missing data period.
- (2) For missing records of CO_2 concentration, stack gas flow rate, percent moisture, fuel usage, and sorbent usage, the substitute data value shall be the best available estimate of the parameter, based on all available process data (e.g., electrical load, steam production, operating hours, etc.). You must document and retain records of the procedures used for all such estimates.

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79150, Dec. 17, 2010]

§ 98.36 Data reporting requirements.

- (a) In addition to the facility-level information required under §98.3, the annual GHG emissions report shall contain the unit-level or process-level emissions data in paragraphs (b) through (d) of this section (as applicable) and the emissions verification data in paragraph (e) of this section.
- (b) Units that use the four tiers. You shall report the following information